

Astm



Astm marka ürünler Özhat tarafından Türkiye'ye paralel ithalat yöntemi ile ithal edilmekte ve siz değerli müşterilerimize en hızlı şekilde teslim edilmektedir. Astm ürünlerinden websitemizde ürün numarası yer almasa bile teklif isteyiniz ; en kısa sürede teklifimiz tarafınıza ulaştırılacaktır.

Astm Ürün Listesi

Referans	Tanım
10046C-C	Thermometer ASTM 46C, Kin Vis @ 50°C, 48.6/51.4°C, 0.05° Division, 305mm lgth, Total Immersion. Supplied with NIST traceable, ISO/IEC 17025 accredited report of calibration at 0, 50, 51°C per ASTM E-1 specifications.
10120C-C	Thermometer ASTM 120C, Kin Vis @ 40°C, 38.6 to 41.4°C, 0.05° Divisions, 305mm lgth, Total Immersion. Supplied with NIST traceable, ISO/IEC 17025 accredited report of calibration at test points of 0, 40, 41°C per ASTM E-1 specifications.
10121C-C	Thermometer ASTM 121C, Kin Vis @ 100°C, 98.6 to 101.4°C, 0.05° Divisions, 305mm lgth, Total Immersion. Supplied with NIST traceable, ISO/IEC 17025 accredited report of calibration at test points of 0, 100, 101°C per ASTM E-1 specifications.
10127C-C	Thermometer ASTM 127C, Kin Vis @ -20°C, -21.4 to -18.6°C, 0.05° Divisions, 305mm lgth, Total Immersion. Supplied with NIST traceable, ISO/IEC 17025 accredited report of calibration at test points of -21, -20, 0°C per ASTM E-1 specifications.
16A5418X022.	spare part for 475-EHS, plug form
2" X 1" S80S	Conc. Red.
2" S80S	Elbow LR90
2" S80S	Tee equal
3" S80S	Cap
30J7506N014.	spare part for 475-EHS, valve body
475-EHS	(control valve, size :2")
A – 615	Q34, 00mm STEEL FLAT IRON - 250,000 Mt
A105	Stopfbuchsenbrille (4)
A335	test pipe – P5B material P9 alloy (6"dia sch 80)
A426 GR CPCA15 154MM	NUT: IMPELLER LOCK LEFT HAND2 OUTSIDE DIAMETER: 115MM/ 117MM INSIDE THREADS: LEFT 100 MM LENGHT
A426 GR CPCA15 USED FOR: OIL TRANSFER PUMP (M1950015-00001) 1"	NUT: IMPELLER LOCK Ø 1" NPTF A276-316 L
A576 GR 1020 Ø150XM57X1.5	NUT: SHAFT LOCKING
A672 Gr. B56 Cl.22	58" Killed Carbon Steel, THK:12.7MM Coating : "densolen primer HT&densolen S-40(STGPS S1)" ASME B31.3

Referans	Tanım
ASTM A283 GRADE C OR ASTM A36	PLATES, CARBON STEEL, FOR GENRAL CARBON STEEL PLATES OF STRUCTURAL APPLICATION THINK: 1 INCH. WIDTH: 4 FT LENGTH: 8 FT
ASTM 2017 #1066109000POS037	PLUNGER PMP FOR SODIUM CHLOURIDE DOSING PUMP, MODEL # MROY XA HP SIMPLEX, KKS: 90GDN40 41AP 001 AT ALSTOM STEAM GENERATING SET MODE L # RT60HDKMD3KND34BUC AT SHOIABA POWER PLANT, STAGE II. DOSAPRO MILTON ROY: DWG#106.6109.000 POS.037
ASTM2240	DUROMETER
D4929	Total chlorine analyzer
NO6002	.Pipe tube – P43 material – Hastelloy SB-622 UNS 16mm dia x 4mm thk
A36 Standart	Kohlenstoff-Strukturstahl
A564 GR 630	Plug Stem (1)
A582 TY 303	Verpackung Follower (23)
FF ANSI B16.21 150#	Dichtung
351 316 S300 T466	Ventil