Özhat İç ve Dış Tic. Ltd. Şti.
Buttim İşmerkezi A Blok Kat:2 No:367 Osmangazi Bursa / Turkey
info@ozhat.com.tr
www.ozhat.com

Atex



Atex marka ürünler Özhat tarafından Türkiyeye paralel ithalat yöntemi ile ithal edilmekte ve siz değerli müşterilerimize en hızlı şekilde teslim edilmektedir Atex ürünlerinden websitemizde ürün numarası yer almasa bile teklif isteyiniz ; en kısa sürede teklifimiz tarafınıza ulaştırırılacaktır

Atex Ürün Listesi

Referans	Tanım
"(M)DEN 1 1/4"	REDUCTION (F)
1 1/4"(M)DEN 1 1/2"	REDUCTION (F)
1099	BAS 99 II 1 GEEX iaIIC
1215 30.1-00/6896 T95°C 24VDC 0,136A	coil 24Vdc
122-800EX	Gerätesteckdose
2X58W	Luminaries
30450245	Aering solenoid valce 115v 60 hz 1/4" Pressure-40 Fuid-AIR
3098X	II 3GEEX naII BAS 99
40722001	SEILLÄNGENGEBER SL3010/GS130 SEIL-D0.8
4206708	(Master card for alarms, Dräger Regard Master Card)
4206717	(Display card for eight channels,)
600X400X250	Armoire
94/9/CE-113	Flange motor "Neri Motori" Type T63B4 N. 0705237 8001 0.18 kW, 230/400 V, 1.2 / 0.7 A;: 1340 s Assy. 63 B5 flange Ex-Est G EExnA11 T4x BDY-4J
AG 00311	(24V,10A Dräger)
APPELTON RW 503E	cable reel
ATEX II 2 G EEX-D IIC T6 ,RAS/AD/103S/CCS	High Quality Catalytic Sensor, Relay Output
BAV370TR11	motor,Drawing No: 806123082
C9505/IS	DIFFERENTIAL PRESSURE GAUGES
C9507/IS	Comark pressure meter (+/-7bar)

Referans	Tanım
D5921-IT1	(EWCT250RNA CEILING/PENDANT LIGHTING FIXTURE FOR DISCHARGE LAMP UP TO 250 W INCLUSIVE OF PROTECTION GUARD (EV 257), HIGH PRESSURE SODIUM LAMP 250 W (E40), ELECTRICAL PARTS (INDUCTIVE BALLAST - 230V-50Hz AND IGNITOR IN A SEPARATE BOX PRE-ASSEMBLED & WIRED TO L.F.), EXT. REFLECTOR (EV 250/8), 2 ENTRIES ø 3/4" (LEFT/RIGHT), 1 STOPPING PLUG ø ¾" AND 1 CABLE GLAND ø ¾" x ARM.CABLE /CW INT. SEAL.RINGS KIT (PMA2NB-KIT - MAT. NICKEL PLATED BRASS) (MATER. CAST ALUMINIUM LIGHT ALLOY + GLASS) (PROT. II 2GD - Ex d IIC T3 - Ex tD A21 IP 66 T200°C) (EXT. COLOUR RAL 9006 - GRAY))
D5921-IT2	(EWCT250RNA CEILING/PENDANT LIGHTING FIXTURE FOR DISCHARGE LAMP UP TO 250 W INCLUSIVE OF PROTECTION GUARD (EV 257), HIGH PRESSURE SODIUM LAMP 150 W (E40), ELECTRICAL PARTS (INDUCTIVE BALLAST - 230V-50Hz AND IGNITOR IN A SEPARATE BOX PRE-ASSEMBLED & WIRED TO L.F.), EXT. REFLECTOR (EV 250/8), 2 ENTRIES ø 3/4" (LEFT/RIGHT), 1 STOPPING PLUG ø ¾" AND 1 CABLE GLAND ø ¾" x ARM.CABLE /CW INT. SEAL.RINGS KIT (PMA2NB-KIT - MAT. NICKEL PLATED BRASS) (MATER. CAST ALUMINIUM LIGHT ALLOY + GLASS) (PROT. II 2GD - Ex d IIC T3 - Ex tD A21 IP 66 T200°C) (EXT. COLOUR RAL 9006 - GRAY))
EN 50 0-14, -18, -20	pressure switch 125Vac 500ma 28VDC IP66
EVAC 301-150NA HPNACJ 55°C	Lantern 150 W SHP explosion
F80-26BMV/V4	Vacuum PUMP.EExd IIB T4 ATEX: 6037 IP55 Power: 0.55 KW Frequency: 50 Hz Voltage: 230 VAC Ampere: 5.6 A Operating Max Temperature: 40 Deg Centigrade Power Factor: 0.7 Weight: 15 Kg
Fluke 28II-EX	Intrinsically safe trms multimeter
G300G	Grid protection galvanized steel forlantern EVAC 301
II 2 G EEXD IIB + H2 T4	Portable hygrometer
LS5130N	Schalter
N.15 LVDT	ATEX zone 22 4..20mA 2 wire, system-powered Course : >= 410 mm Precision : < 1 mm
TM-FM-FML250-AL-LP-3EE-220CS-12-S1-D2	ISL FLOW METER,Model: FML-250-AL-LP-3EE 220CS-12-S1-D2
VPS 5810SP	(Pressure sensor IG, -100 to 300mBar)
XCW-A115, 03ATEX0083 X obsolete/replacement LS5130	Positionsschalter mit Standardrollen
XCWF103	(LIMIT SWITCH ATEX II 2 GD T85°)
EX II 2G EEX IIA T3	SOCKET
DN 15	Ventil für Wasserstoffgas
DN 25	Ventil für Wasserstoffgas
DN 40	Ventil für Wasserstoffgas
DN 50	Ventil für Wasserstoffgas
CTM-2400-TR	Wi-Fi explosionsgeschützte Antenne
SX27RV120	Sensor
EXD-2024	Power-Stecker
EX-0357	Power-Stecker
LS 5130	Schalter

Referans	Tanım
6-C-FV-0093	REGELVENTIL
0563	Nass Magnet Solenoid Spule
E0497_1 - 1182512 - Ex RC Si M30 2Ö-3G/D-5m	Sensor
E0497_2 - 1180333 - Ex MC 30	Magnet
827A.X4-00H-M10-G	DIGITALER STELLUNGSREGLER
E 604 T - replaced by PLATE634T2B	E-Atex-Bereich Niederdruck-Platten-Axialventilatoren
PLATE634T2B	AXIALVEN
2G-EEXDEIIBTE	Motor 0,18kW
E0743_1 - PRS71 500.A IIB 4-1.5T	Ventilator
E0743_2	PASSEND ZU
I I 1GD T6	Clips
E0743_5 - PRS71 400.A IIB 4-0.55T	Ventilator
0.25kW 230/400V tri 750tr/min B35	Motor-
PM880	PORTABLE HYGROMETER
TS293KM	Gas-Sensor
TRCG12G21009	Poyamid Kabel
242149	NEOPRENE SEAL PG21
282104	NUT PG21
M5 555x690x96mm	MacroPac
STAH6042/7 obsolete, alternative BAY51-36-2X	LEUCHTSTOFFLAMPE
EVC5AC	Impulssteuerung