Özhat İç ve Dış Tic. Ltd. Şti.
Buttim İşmerkezi A Blok Kat:2 No:367 Osmangazi Bursa / Turkey
info@ozhat.com.tr
www.ozhat.com

Stafsjö



Stafsjö marka ürünler Özhat tarafından Türkiyeye paralel ithalat yöntemi ile ithal edilmekte ve siz değerli müşterilerimize en hızlı şekilde teslim edilmektedir Stafsjö ürünlerinden websitemizde ürün numarası yer almasa bile teklif isteyiniz ; en kısa sürede teklifimiz tarafınıza ulaştırırılacaktır

Stafsjö Ürün Listesi

Referans	Tanım
CUZN39PB3/SS5170	Stem nut Brass (montage image pose 4)
DN 150/ PN 16	Manual knife gate valve./1.4404/ between flanges
DN 300/ PN 16	Manual knife gate valve
DN 350/ PN 16	Manual knife gate valve
KNIFE GATE VALVE MVE NOM. DIAMETER: DN 150 FACE TO FACE: STAFSJO STANDARD NOM. PRESSURE: PN 10/16 99	knife gate valve MVE nom. diameter: DN 150 face to face: STAFSJÖ standard nom. pressure: PN 10/16 body: stainless steel 1.4408 gate: stainless steel 1.4404 sealing: metal to metal packing: Twin PackTM actuator: pneumatic, single acting, spring to close, control pressure min. 5 bar(g) material actuator: stainless steel AISI 304
RKO-A SIZE DN/NPS: 200 PN (BOLT CIRCLE): PN 10 - EN 1092-1	Stafslo knife gate valve RKO-A Size DN/NPS: 200 PN (bolt circle): PN 10 - EN 1092-1 Installation lenght : work standard 60 mm Body material: ENJL1030 (GG20) Gate valve plate material: 1.4462 Gate valve plate surface: hard chrome plated Gland packing: 1.4408 Seal: polyurethane Packing: TwinPack (TY) differential pressure max.: 6.0 bar - in preferred direction Operating pressure max.: 6.0 bar Fitting type: beams, aluminium anodized with tie rods 1.4301 Bore in beams: D= 28 mm open/closed Screw fitting: stainless steel A2 Protective device material: 1.4301 Piston rod material: 1.4104 actuation: pneumatic actuator ECM160 double acting, incl. Magnetic piston, operating pressure 5- 7 bar
SE 61895	Knife gate valve