Özhat İç ve Dış Tic. Ltd. Şti.
Buttim İşmerkezi A Blok Kat:2 No:367 Osmangazi Bursa / Turkey
info@ozhat.com.tr
www.ozhat.com

Stewart Buchanan

STEWART BUCHANAN

ORIJINAL YEDEK PARÇALAR

Stewart Buchanan marka ürünler Özhat tarafından Türkiyeye paralel ithalat yöntemi ile ithal edilmekte ve siz değerli müşterilerimize en hızlı şekilde teslim edilmektedir Stewart Buchanan ürünlerinden websitemizde ürün numarası yer almasa bile teklif isteyiniz ; en kısa sürede teklifimiz tarafınıza ulaştırırılacaktır

Stewart Buchanan Ürün Listesi

Referans	Tanım
1122	Pressure Indicator- 700KPA,70C,1/2 NPTM
20041361	DP GAUGES, Range: 0 to 30 Bar; ADD_INFO: ½ IN NPT, 316 SS TUBE
2050	Temperature Indicator 700kpa,70C, 2 150# ANSI
316 GS	gauge
A9021/3 - obsolete, replaced by Model 522/GF	GAUGE PRESSURE: 0-100 PSI; 4" DIAL; 3/8" NPT; SS CASE; BOTTOM; GLYCERINE FILLED; STD INTERNALS
CPS1147	GAUGE,PR,0-16KG/CM2,1/2"NPT,SRF,4",SS Dial Size : 4 IN (100 MM) Input Pressure Range : 0 - 16 KG/CM2 Material, Wetted Part : SS 316
MGS20/A, P/N:02857K80	GAUGE,PR,0-10KG/CM2,1/2"NPT,BTM,4",SSL
Model 1122 / GF	100mm dia Glycerine Filled Gauge. Direct Mounting, Bottom connection 1 / 2” NPT Male. 316 Stainless Steel case, bourdon tube and socket. Full safety pattern, solid front, laminated safety glass window and blowout back. Range 0-4000 kPa
MODEL 2032	100MM Dial Filled System Diaphragm Seal Gauge. Direct Mounting. Stainless steel case, tube, socket and movement, bottom connection. Blow out device on top of case. Fill fluid : Octoil suitable for temperatures up to 400 Deg C. 316 stainless steel diaphragm seal unit and wetted parts terminating 1/2" NPT.
101039/TR/EXP Model 522/GF (Range 0-100 PSI)	Direktmontage des mit Glyzerin gefüllten Manometers
RANGE 0-1 BAR	100MM Dial Glycerine Filled Gauge Direct Mounting. Bottom connection 1/2" BSP. 316 Stainless Steel case, tube, socket & 304 s/s movement. Full safety pattern, solid front, safety window and blow-out back. Model 1122/GF C/w 1/2" BSP Male / Female Overrange Gauge Protector In AISI 316 Stainless steel Rated 6000 PSI. Set Point 1 BAR. Model ILORGP
RANGE 0-10 BAR	100MM Dial Glycerine Filled Gauge Direct Mounting. Bottom connection 1/2" NPT. 316 Stainless Steel case, tube, socket & 304 s/s movement. Full safety pattern, solid front, safety window and blow-out back. Model 1122/GF
RANGE 0-100 BAR	100MM Dial Glycerine Filled Gauge Direct Mounting. Bottom connection 1/2" NPT. 316 Stainless Steel case, tube, socket & 304 s/s movement. Full safety pattern, solid front, safety window and blow-out back. Model 1122/GF

Referans	Tanım
RANGE 0-16 BAR	100MM Dial Glycerine Filled Gauge Direct Mounting. Bottom connection 1/2" NPT. 316 Stainless Steel case, tube, socket & 304 s/s movement. Full safety pattern, solid front, safety window and blow-out back. Model 1122/GF
SW-07M08F-AI-MK2	1 / 2” NPT Male x 1 / 2” BSP Female ‘SWIVADAPT’ MK2 Swivel Gauge Adaptor in AISI 316 Stainless Steel. Rated 10,000 PSI.
1122/GF/ORGP	MESSGERÄT, DRUCK
632/GF	100mm MANOMETER