



ROSTFREI  
Inox  
Stainless  
Steel

- 4 Type**
- A 2x2 bores for countersunk screws
  - C 2x2 threaded studs

**2 3**

l <sub>1</sub>	l <sub>2</sub>	Material						d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> +0,5	l <sub>3</sub>			l <sub>4</sub>		m <sub>1</sub>	m <sub>2</sub>
		Type A			Type C										ZD, AL	NI, A4	ZD	NI			
30	30	ZD	NI	A4	AL	-	-	-	4,3	3	7,5	4	4,5	8,5	10,7	10,7	-	-	18	18	
40	40	ZD	NI	A4	AL	ZD	NI	M 5	5,3	4	9	5	5,5	11	14	16	12	11	25	25	
50	50	ZD	NI	A4	AL	ZD	NI	M 6	6,4	6	11,5	6	6,5	13	18,5	21	12	13	30	30	
60	60	ZD	NI	A4	AL	ZD	NI	M 8	8,3	8	15	8	8,5	17	21,5	26	14	17	36	36	

**Specification**

**1 5**

- Zinc die casting **ZD**
  - plastic coated
  - black, RAL 9005, textured finish ● **SW**
  - silver, RAL 9006, textured finish ● **SR**
  - chrome-plated ● **CR**
- Stainless Steel
  - AISI CF-8 **NI**
  - German Material No. 1.4408 **A4**
  - matt blasted **GS**
- Aluminum **AL**
  - anodized, natural colour ● **EL**
- Pin
  - Stainless Steel AISI 303 for ZD
  - Stainless Steel AISI 316Ti (A4) for AL, NI and A4
- Threaded stud (Type C)
  - Stainless Steel AISI 316 for ZD and AL
  - Stainless Steel AISI CF-8 for NI, casted „in one piece“
- *Stainless Steel characteristics* → Page 334
- *Load rating information* → Page 348
- **RoHS compliant**

**Information**

GN 237 hinges are characterized by their compact and stable design. The various material and surface choices in combination with two mounting types enable very specific applications.

see also...

- *Hinges GN 337 (detachable)* → Main Catalogue Page 877
- *Hinges GN 238 (adjustable)* → Main Catalogue Page 880

**How to order**

**GN 237-ZD-60-60-A-SR**

1	Material
2	l <sub>1</sub>
3	l <sub>2</sub>
4	Type
5	Finish